



MAGNETIC LEVEL GAUGE

PN40 / Class 300

DS MG - DS MP

Code: DS MG - DSMP - ... /40/RF - M...- SS/SS/.../SS



Technical data

Service conditions

Pressure: Standard PN40

On request Class 300

Temperature: Standard up to 200°C

On request up to 230°C

Specific weight: $\geq 0,7 \text{ g/cm}^3$

View

Standard: adjustable on 360° in the installation phase

Distance M (Centre-to-centre)

On request, distances up to 5.600 mm in one sole piece (Fixed distance, not adjustable)

Option: On request distances over 5.600 mm (Execution in several pieces)

Materials (Standard)

Main chamber:

Stainless steel 316L ($\varnothing 60,3 \times 2,77 \text{ mm}$)

Float:

Titanium Grade 2 ($\varnothing 50 \text{ mm}$) with reinforcements

Process connections:

Stainless steel 316L (flanged, threaded pipes, butt weld pipes)

With shut-off cocks DS GR18 in carbon steel ASTM A105 or stainless steel 316L

Rollers:

Brass with red and white epoxy paint, anodised aluminium housing, glass cover

Gaskets

Standard: graphite/AISI 316

Options: PTFE/AISI 316

Process connections

Standard flanges:

UNI PN40 DN15-20-25

ANSI #300/RF DN $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

Standard threaded pipes:

BSP-M $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

NPT-M $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

BSP-F $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

NPT-F $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

Standard butt weld pipes:

BW $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

SW $\frac{1}{2}$ " - $\frac{3}{4}$ " - 1"

Options: further connections type or connections with cocks (See details at page 2.13 and 2.14)

Vent: Standard: threaded $\frac{1}{2}$ " with plug

Options: On request, with flange or with cock DS D12 (See details at page 2.13 and page 2.14)

Drain: Standard: threaded $\frac{1}{2}$ " with plug

Options: On request, with flange or with cock DS D12 (See details at page 2.13 and page 2.14)

Process connections with shut-off cocks: (See details at page 2.13 and page 2.14)

Cocks DS GR18: cylindrical plug type - Straight type - Quick 90° closing

Dimensions

B = Distance depending on the specific weight of the fluid

T = 130 mm (Standard); Option: on request

S = 100 mm (Standard); Option: on request

Accessories

Shut-off cocks

(See details from page 2.13)

Drain cock

(See details from page 2.13)

Vent cock

(See details from page 2.13)

Calibrated scale

(See details from page 2.14)

Magnetic switches

(See details from page 2.15)

Level transmitter

(See details from page 2.30)

Weights

Magnetic level gauge: Kg. 12,0 approx. (With centre-to-centre 1.000 mm and flanges DN20 PN40)

Cocks DS GR18: Kg. 6,2 approx. (With flanges UNI DN20 PN40)

Spare parts

For routine maintenance are not necessary spare parts.

For cocks and valves see from page 1.72 of the catalogue relative to the glass level gauges.